



Main

Range of product	INS250 INS320...630 INS40...160 INS630b...2500 INV100...250 INV320...630 INV630b...2500 NG160 NG160NA NR100...250 NR400...630 NSC100 NSX100...250 NSX400...630 Easypact CVS100...250 Easypact CVS400...630 PowerPact multistandard
Device short name	OF SD SDE SDV
Product or component type	Auxiliary contact
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Early-break Early-make
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	DC-14: 1 A DC 24 V DC-14: 0.2 A DC 48 V DC-14: 0.05 A DC 110 V DC-14: 0.03 A DC 250 V DC-12: 6 A DC 24 V DC-12: 2.5 A DC 48 V DC-12: 0.6 A DC 110 V DC-12: 0.3 A DC 250 V AC-15: 6 A AC 50/60 Hz 48 V AC-15: 6 A AC 50/60 Hz 24 V AC-15: 5 A AC 50/60 Hz 110 V AC-15: 4 A AC 50/60 Hz 220/240 V AC-15: 2 A AC 50/60 Hz 380/440 V AC-15: 1.5 A AC 50/60 Hz 480 V AC-15: 0.1 A AC 50/60 Hz 660/690 V AC-12: 6 A AC 50/60 Hz 660/690 V AC-12: 6 A AC 50/60 Hz 480 V AC-12: 6 A AC 50/60 Hz 48 V AC-12: 6 A AC 50/60 Hz 380/440 V AC-12: 6 A AC 50/60 Hz 24 V AC-12: 6 A AC 50/60 Hz 220/240 V AC-12: 6 A AC 50/60 Hz 110 V
Minimum load	100 mA at 24 V
Product compatibility	PowerPact H-Frame PowerPact J-Frame PowerPact L-Frame

Contractual warranty

Period	18 months
--------	-----------