



## Main

Range of product	IC60 IID ISW-NA
Device short name	IOF/SD+OF
Signal contacts composition	2 C/O
[Ie] rated operational current	AC-12: 3 A AC 50/60 Hz 415 V AC-12: 6 A AC 50/60 Hz 240 V DC-12: 1 A DC 130 V DC-12: 1.5 A DC 60 V DC-12: 2 A DC 48 V DC-12: 6 A DC 24 V
9 mm pitches	1

## Complementary

Product or component type	Double OC or fault contact
[Ui] rated insulation voltage	4 kV
Local signalling	Mechanical indicator
Mounting mode	Fixed
Width	9 mm
Colour	White
Auxiliary connection terminal	Control circuit: tunnel type terminals 4 mm <sup>2</sup>
Wire stripping length	10 mm
Tightening torque	1 N.m

## Environment

RoHS EUR status	Compliant
RoHS EUR conformity date	1001

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.