



Main

Range	ComPacT new generation
Product name	ComPacT NSX new generation
Device short name	NSX400NA
Product or component type	Switch disconnecter
Device application	Distribution
Poles description	3P
[I _{th}] conventional free air thermal current	400 A at 50 °C
[I _e] rated operational current	AC-22A: 400 A AC 50/60 Hz 220...690 V AC-23A: 400 A AC 50/60 Hz 220...690 V
[U _e] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Suitability for isolation	Yes conforming to EN/IEC 60947-3
Utilisation category	AC-22A AC-23A
Breaking capacity code	NA
Contact position indicator	Yes
Visible break	No
Mounting mode	Fixed
[I _{cw}] rated short-time withstand current	5 kA during 1 s 5 kA during 3 s 1.93 kA during 20 s
[I _{cm}] rated short-circuit making capacity	330 kA with upstream protection circuit breaker 7.1 kA switch-disconnector alone
Control type	Toggle
[U _i] rated insulation voltage	800 V AC 50/60 Hz
[U _{imp}] rated impulse withstand voltage	8 kV

Complementary

Mounting support	Backplate
Upside connection	Front
Downside connection	Front
Connection pitch	45 mm
Mechanical durability	15000 cycles
Electrical durability	AC-22A: 10000 cycles 440 V AC 50/60 Hz In/2 AC-22A: 2500 cycles 690 V AC 50/60 Hz In AC-22A: 5000 cycles 440 V AC 50/60 Hz In AC-22A: 5000 cycles 690 V AC 50/60 Hz In/2 AC-23A: 10000 cycles 440 V AC 50/60 Hz In/2 AC-23A: 2500 cycles 690 V AC 50/60 Hz In AC-23A: 5000 cycles 440 V AC 50/60 Hz In AC-23A: 5000 cycles 690 V AC 50/60 Hz In/2
Width (W)	140 mm
Height (H)	255 mm
Depth (D)	110 mm
Net weight	5.2 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Standards	EN/IEC 60947-1 EN/IEC 60947-3
Product certifications	CE EAC CCC

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60664-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.0 cm
Package 1 Width	16.0 cm
Package 1 Length	29.5 cm
Package 1 Weight	5.333 kg
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	11.369 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------